






Bimetal Thermometer

雙金屬溫度計

雙金屬溫度計 BIMETAL THERMOMETER

B

外觀 APPEARANCE			
型號 MODEL	MB-200 BS-TYPE 底部出口 Bottom entry	MB-201 BL TYPE 背部出口 Back entry	MB-202 BA TYPE 可調角 Adjustable angle
溫度範圍 TEMP. RANGE	4" 面 -20 ~ 80 °C -20 ~ 120 °C -50 ~ 50 °C -50 ~ 300 °C	0 ~ 50 °C 0 ~ 100 °C 0 ~ 120 °C 0 ~ 150 °C	0 ~ 200 °C 0 ~ 250 °C 0 ~ 300 °C 0 ~ 400 °C
外殼及感溫棒材質 Material of case and Stem	SUS304	SUS304	SUS304
感溫棒管徑 OUT DIA. OF STEM	Φ 6.35 ~ 9.5 mm	Φ 6.35 ~ 9.5 mm	Φ 6.35 ~ 9.5 mm
感溫棒長度 LENGTH OF STEM	2.5" L ~ 50" L	2.5" L ~ 50" L	2.5" L ~ 50" L
準確度 ACCURACY	± 1%	± 1%	± 1%
備註 NOTE	<p>A. 訂購請告知(1)型號(2)溫度範圍(3)感溫棒管徑及長度(4)面板尺寸(5)其他特殊規格 (When Ordering (1) Model (2)Temp.Range(3)Dial & Length of Stem (4) The size of Dial (5)Other spec.as need)</p> <p>B. 面板: 2"-3" 附1/4"PT牙 · 4"-6" 附1/2"PT牙 (Thread Connection 2"-3" dial with 1/4" PT , 4"-6" dial with 1/2" PT)</p> <p>C. 面板: 3" OD為81mm, 4" OD為119mm, 5" OD為 141mm</p>		



隔測溫度計 Gas Actuated Dial Thermometer

外觀 APPEARANCE			
型號 MODEL	MA-102H 壁掛型 HANGING TYPE		MA-102M 埋入型 MOUNTING TYPE
溫度範圍 TEMP. RANGE	4" 面 -20 - 80 °C 0 - 50 °C -20 - 120 °C 0 - 100 °C -50 - 50 °C 0 - 120 °C -50 - 300 °C 0 - 150 °C		0 - 200 °C 0 - 500 °C 0 - 250 °C 0 - 600 °C 0 - 300 °C 0 - 400 °C
材質 MATERIAL	外殼及感溫管 : SUS304 Case & stem : SUS304		外殼及感溫管 : SUS304 Case & stem : SUS304
感溫棒管徑 OUT DIA OF STEM	ϕ 6.35 ~ 12 mm		ϕ 6.35 ~ 12 mm
毛細管長度 LENGTH OF SPIRAL	標準長:3M 最長:20M Standard 3M, MAX 20M		標準長:3M 最長:20M Standard 3M, MAX 20M
準確度 ACCURACY	$\pm 1\%$		$\pm 1\%$
備註 NOTE	A 訂購請告知: (1)型式(2)溫度範圍 (3)感溫棒管徑 (5)面板尺寸(4)毛細管長度 (6)其他特殊規格 (When Ordering (1) Model (2)Temp.Range(3)Dial of Stem (4) Length of spiral (5)The size of Dial (6)Other spec.as need)	B 面板: 4" 附 1/2" PT牙, 6" 附 3/4" PT牙 (With a 1/2"PT screw nut for 4" dial , With a 3/4"PT screw nut for 6" dial)	C 可附加電器接點: 0.4A / AC110V , 0.2A / AC220V (Electric Contact 0.4A / AC110 , 0.2A / AC220V)

B