






# Bimetal Thermometer

## 雙金屬溫度計

### 雙金屬溫度計 BIMETAL THERMOMETER

B

外觀 APPEARANCE			
型號 MODEL	<b>BS-TYPE (MB-200)</b> 底部出口 Bottom entry	<b>BL TYPE (MB-201)</b> 背部出口 Back entry	<b>BA TYPE (MB-202)</b> 可調角 Adjustable angle
溫度範圍 TEMP. RANGE	-50 ~ +600 °C	-50 ~ +600 °C	-50 ~ +600 °C
外殼及感溫棒材質 Material of case and Stem	SUS304	SUS304	SUS304
感溫棒管徑 OUT DIA. OF STEM	φ 6.35 ~ 9.5 mm	φ 6.35 ~ 9.5 mm	φ 6.35 ~ 9.5 mm
感溫棒長度 LENGTH OF STEM	2.5 "L ~ 50" L	2.5 "L ~ 50" L	2.5 "L ~ 50" L
準確度 ACCURACY	± 1%	± 1%	± 1%
備註 NOTE	<p><b>A.</b> 訂購請告知(1)型號(2)溫度範圍(3)感溫棒管徑及長度(4)面板尺寸(5)其他特殊規格 ( When Ordering (1) Model (2)Temp.Range(3)Dial &amp; Length of Stem (4) The size of Dial (5)Other spec.as need )</p> <p><b>B.</b> 面板: 2"-3" 附1/4"PT牙, 4"-6" 附1/2"PT牙 ( Thread Connection 2"-3" dial with 1/4" PT , 4"-6" dial with 1/2" PT )</p>		



### 隔測溫度計 Gas Actuated Dial Thermometer

外觀 APPEARANCE		
型號 MODEL	<b>MA-102H</b> 壁掛型 HANGING TYPE	<b>MA-102M</b> 埋入型 MOUNTING TYPE
溫度範圍 TEMP. RANGE	-50 ~ +650 °C	-50 ~ +650 °C
材質 MATERIAL	外殼及感溫管 : SUS304 Case & stem : SUS304	外殼及感溫管 : SUS304 Case & stem : SUS304
感溫棒管徑 OUT DIA OF STEM	φ 6.35 ~ 12 mm	φ 6.35 ~ 12 mm
毛細管長度 LENGTH OF SPIRAL	標準長:3M 最長:20M Standard 3M, MAX 20M	標準長:3M 最長:20M Standard 3M, MAX 20M
準確度 ACCURACY	± 1%	± 1%
備註NOTE	<p>A 訂購請告知:                      (1)型式(2)溫度範圍                      (3)感溫棒管徑                      (5)面板尺寸(4)毛細管長度                      (6)其他特殊規格                      ( When Ordering (1) Model                      (2)Temp.Range(3)Dial of                      Stem (4) Length of spiral                      (5)The size of Dial (6)Other                      spec.as need )</p> <p>B 面板:                      4" 附 1/2" PT牙,                      6" 附 3/4" PT牙                      ( With a 1/2"PT                      screw nut for 4" dial ,                      With a 3/4"PT screw                      nut for 6" dial )</p> <p>C 可附加電器接點:                      0.4A / AC110V ,                      0.2A / AC220V                      ( Electric Contact                      0.4A / AC110 ,                      0.2A / AC220V )</p>	

B