



RENSE (High Temperature Type)

CE-approval

CE-認證

Relative Humidity & Temperature Transmitters Series 741 and 740
荷蘭RENSE 高温型 相對濕·溫度傳送器 741/740 系列



高温型分離式
High Temp. - Remote



高温型管路式
High Temp. Duct-Mount

Features特點

- High Temperature Model up to 150°C (300°F)
高温型機種可量測至150°C (300°F)
- EMC Immunity to EN 50082-1
符合 EMC EN 50082-1
- Series 741: 2-Wire 4~20mA output
741 系列: 2線式4~20mA輸出
- Series 740: User-Selectable Signals
740 系列: 使用者可選擇輸出信號
- User-Selectable Temperature Range
使用者可選擇溫度範圍
- Optional available are adjustable mounting flanges or a 3/4" NPT Adjustable Stainless Steel Fitting
可選擇活動式法蘭安裝或3/4" NPT 不銹鋼活動牙安裝
- The maximum tip-temperature for High Temperature Duct- or Remote-Mount is 150°C (300°F)
感應頭需耐最高溫150°C時,請選用高温型管路式或分離式

D

ORDERING INFORMATIONS 選購機型代號

Description敘述	2-Wire Transmitter 2線式傳送器	3/4Wire Transmitter 3/4線式傳送器	備註
Wall -Mount RH Transmitter 壁掛型濕度傳送器	HX -741-T-00	HX -740-T-00	Polycarbonate Housing IP65 IP65等級
Wall -Mount RH +Temp. Transmitter 壁掛型溫濕度傳送器	HT -741-T-00	HT -740-T-00	Polycarbonate Housing IP65 IP65等級
High Temp. Duct-Mount RH Transmitter L=300mm 高温風管型濕度傳送器	HX -741-T-02	HX -740-T-02	Max.Temp. tube/tip 150 °C 最大耐溫 150 °C
High Temp. Duct-Mount RH +Temp. Transmitter L=300mm 高温風管型溫濕度傳送器	HT -741-T-02	HT -740-T-02	Max.Temp. tube/tip 150 °C 最大耐溫 150 °C
Remote RH Transmitter 7/8"-14 UNF 高温分離型濕度傳送器 7/8"-14 UNF 螺牙	HX -741-T-04	HX -740-T-04	High Temp. probe (up to 150°C) 最大耐溫 150 °C
Remote RH +Temp. Transmitter 7/8"-14 UNF 高温分離型溫濕度傳送器 7/8"-14 UNF螺牙	HT -741-T-04	HT -740-T-04	High Temp. probe (up to 150°C) 最大耐溫 150 °C